

TX-1919RGBW40D180-001H90

PRODUCT SPECIFICATION

Features:

- ◆ Excellent transiting heat from LED chip operating under RGB:350 mA W:700 mA.
- ◆ Mixing any two colors of light, there will be no partial color and color spots uneven phenomenon.
- ◆ High luminous output.
- ◆ No UV.
- ◆ Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆ Red: AlGaInP
- ◆ Green: GaInN
- ◆ Blue: GaN
- ◆ White: GaN


Emitting Color:

- ◆ Red
- ◆ Green
- ◆ Blue
- ◆ white

Applications:

- ◆ Entertainment lighting
- ◆ Landscape lighting
- ◆ Commercial lighting
- ◆ Decorative lighting

Package Dimensions:



Notes:

1. All dimensions are in millimeters .
2. Tolerances unless otherwise mentioned are ± 0.1 mm .

Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbol	Ratings	Unit	
Forward Current	IF	R	350	mA
		G	350	
		B	350	
		W	700	
Reverse Voltage	VR	Not designed for reverse operation	V	
Power Dissipation	PD	R	8000	mW
		G	8000	
		B	8000	
		W	16000	
Junction Temperature	Tj	R	115	°C
		G	150	
		B	150	
		W	150	
Electrostatic Discharge Threshold (ESD)	ESD	2000	V	
Storage Temperature	Tstg	-20~+70	°C	
Operation Temperature	Topr	-40~+100		

Notes:

- Specifications are subject to change without notice.
- Under the stipulated Characteristics parameters above, the life span of the LED is more than 50,000hours.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:
 STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Part No.	TX-1919RGBW40D180-001H90	Spec No.	WKF-BF0321	Page	3 of 7
----------	--------------------------	----------	------------	------	--------

Electrical Optical Characteristics (Tc=25°C)



Parameter	Symbol	Condition	Emitting Color	Min.	Typ.	Max.	Units
Luminous Flux	ϕ_v		R	320	450	—	lm
			G	480	650	—	
			B	88	115	—	
			W	640	850	—	
Dominant Wavelength	λ_d		R	618	623	628	nm
			G	522	525	528	
			B	452	455	457	
Correlated Colour Temperature	CCT		W	4100	4200	4300	K
Color Rendering Index	Ra	$I_{f(RGB)}=350mA$	W	90	92.5	—	—
Peak-emission Wavelength	λ_p	$I_{f(W)}=700mA$	R	627	632	637	nm
			G	515	520	525	
			B	447	452	457	
Spectral Line Half-Width	$\Delta\lambda$		R	15	20	25	nm
			G	25	30	35	
			B	15	20	25	
			W	22	27	32	
Forward Voltage	V_f		R	20	21.5	23	V
			G	20	21.5	23	
			B	20	21.5	23	
			W	20	21.5	23	
Viewing Angle at 50 % IV	$2\theta_{1/2}$	—	—	—	120	—	Deg
Thermal Resistance Junction to Case	$R_{\theta J-C}$	$I_{f(RGB)}=350mA$	—	—	1.5	—	K/W
Temperature Coefficient of Voltage	$V\Delta F/T$	$I_{f(W)}=700mA$	—	—	-2	—	mV/°C

Notes:


- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance:±15%.
- 4.Forward voltage measurement tolerance:±0.15V.

Typical Electrical/Optical Characteristics Curves


(25°C Ambient Temperature Unless Otherwise Noted)




Temperature VS. Forward Voltage (IF_(RGB)=350mA IF_(W)=700mA)




Temperature VS. Relative Luminous Flux (IF_(RGB)=350mA IF_(W)=700mA)



Relative Spectral Distribution



Beam Pattern
0°



Notes:

1. $2\theta_{1/2}$ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is $\pm 5^\circ$.