

TX-1524SW11F13-08H982760

PRODUCT SPECIFICATION

Features:

- ◆Excellent transiting heat from LED chip operating under 800mA.
- ◆Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- ◆High luminous output.
- ◆No UV.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆GaInN


Emitting Color:

- ◆White
- ◆Warm white

Applications:

- ◆Commercial lighting
- ◆General Lighting

Package Dimensions:




W: Warm White ; C: White

Notes:

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are $\pm 0.25\text{mm}$.

Connections:



Code Formats:

TX-1524SW11F13-08H982760

TX	—	15	24	SW	11	F	13	—	08	H98	2760
TYANSHINE	—	series	Watt type	performance	LES	chip code	die count in series	—	BOM	Ra	CCT

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Forward Current	IF	800	mA
Reverse Voltage	VR	Not designed for reverse operation	V
Power Dissipation	PD	W	W
		C	
		W+C	
Junction Temperature	Tj	W	℃
		C	
Case Temperature (C)	Tc	85	℃
Electrostatic Discharge Threshold (ESD)	ESD	2000	V
Storage Temperature	Tstg	-30~+80	℃
Operation Temperature	Topr	-30~+85	

Notes:



- Specifications are subject to change without notice.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:
STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	ϕ_v	If=500mA	W	1350	1550	1750	lm
			C	1700	1950	2200	
Forward Voltage	V_f		W	35	37	39	V
			C	35	37	39	
Correlated Colour Temperature	CCT		W	2660	2730	2800	K
			C	5750	6000	6300	
Viewing Angle at 50 % IV	$2\theta_{1/2}$		W	—	115	—	Deg
			C	—	115	—	
Reverse Current	I_R	—	—	—	—	μA	
Thermal Resistance Junction to Case	$R\theta_{J-C}$	—	—	—	1.45	—	K/W
Color Rendering Index	Ra	If=500mA	W	97	—	—	—
			C	97	—	—	

Notes:


- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance: $\pm 15\%$.
- 4.Forward voltage measurement tolerance: $\pm 3\%$.
- 5.Ra measurement tolerance: ± 2 .



Notes:

1. $2\theta_{1/2}$ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is $\pm 5^\circ$.

Chromaticity Coordinates (Condition : IF=500mA , Tc=25℃)




Notes:

1. chromaticity (x, y) measurements tolerance: ± 0.005 .

Dimensions For Cannulation And Packaging

Quantity: 36PCS



Notes:

- 1. All dimensions are in millimeters.
- 2. Tolerances are ± 2.0 mm unless otherwise noted.
- 3. The products are packaged together with silica gel, Transport, not to the weight of welding LED light-emitting area, As a result of the weight of LED light-emitting zone in the quality of, Irresponsible of the Company.