

TX-H1936SW17A-2760V39-02H95

PRODUCT SPECIFICATION

Features:

- ◆Excellent transiting heat from LED chip operating under 1200mA.
- ◆Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- ◆High luminous output.
- ◆No UV.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆GaInN


Emitting Color:

- ◆White
- ◆Warm white

Applications:

- ◆Commercial lighting
- ◆General Lighting

Package Dimensions:



I: Warm White(S) II: White(W)

Notes:

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are ±0.25mm .

Code Formats:

TX-H1936SW17A-2760V39-02H95

TX	—	H	19	36	SW	17	A	—	2760	V39	—	02	H95
TYANSHINE	—	high density	series	watt type	performance	LES	texture	—	CCT	VOL TS	—	BOM	Ra
Part No.	TX-H1936SW17A-2760V39-02H95					Spec No.	WKF-DA0132			Page	2 of 9		

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Forward Current	IF	1200	mA
Reverse Voltage	V _R	Not designed for reverse operation	V
Power Dissipation	P _D	S	W
		W	
		S+W	
Junction Temperature	T _j	S	℃
		W	
Case Temperature (C)	T _c	85	℃
Electrostatic Discharge Threshold (ESD)	ESD	2000	V
Storage Temperature	T _{stg}	-30~+80	℃
Operation Temperature	T _{opr}	-30~+85	

Notes:

- Specifications are subject to change without notice.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:
STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units	
Luminous Flux	φ_v	If=1000mA	S	3200	3600	4000	lm	
			W	4000	4400	4900		
Forward Voltage	V_f		S	34	36	38	V	
			W	34	36	38		
Correlated Colour Temperature	CCT		S	2620	2700	2760	K	
			W	5750	6000	6300		
Viewing Angle at 50 % IV	$2\theta_{1/2}$		S	—	115	—	Deg	
			W	—	115	—		
Reverse Current	I_R		—	—	—	—	—	μA
Thermal Resistance Junction to Case	$R\theta_{J-C}$		—	—	—	0.61	—	K/W
Color Rendering Index	Ra		If=1000mA	S	95	—	—	—
				W	95	—	—	


Notes:

- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance:±15%.
- 4.Forward voltage measurement tolerance:±3%.
- 5.Ra measurement tolerance: ±2.


Typical Electrical/Optical Characteristics Curves



(25°C Ambient Temperature Unless Otherwise Noted)


Forward Current VS. Forward Voltage



Forward Current VS. Relative Luminous Flux








Notes:

- 1. $2\theta_{1/2}$ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
- 2. View angle tolerance is $\pm 5^\circ$.

Chromaticity Coordinates (Condition: IF=1000mA, Tc=25℃)



Notes:


1. chromaticity (x, y) measurements tolerance: ± 0.005 .

Reliability Test

Test Item		Test Condition			
Continuous Operation Test		IF=1000mA Ta=25℃ ×1000hrs			
Low Temperature Storage Test		-30℃ × 1000 hours			
High Temperature Storage Test		100 ℃ × 1000 hours			
Moisture-proof Test		85 ℃, 85 %RH for 500 hours			
Thermal Shock Test		-40 ℃ × 15 minutes – 125 ℃ × 15 minutes, 100 cycle			
Part No.	TX-H1936SW17A-2760V39-02H95	Spec No.	WKF-DA0132	Page	8 of 9

Dimensions For Cannulation And Packaging

Quantity: 36PCS



Notes:

- 1. All dimensions are in millimeters.
- 2. Tolerances are ± 2.0 mm unless otherwise noted.
- 3. The products are packaged together with silica gel, Transport, not to the weight of welding LED light-emitting area, As a result of the weight of LED light-emitting zone in the quality of, Irresponsible of the Company.